

Telephone +44 (0) 1353 661111

Email

Fax

+44 (0) 1353 662370 sales@standen.co.uk



Standen QM Potato Harvester

Standen QM Harvester Standard Specification	
Power Requirements	From 65hp
Open Front End	1500mm wide front share and web for crops grown in 26- 36"rows or beds
Controls	Electronic in-cab control box
Drawbar	Hydraulic Adjustment
Depth Control	Automatic depth sensing
Intake Discs	Independent spring loaded fitted on a live floating chassis. Fitted with scrapers
Shares	1 or 2 piece independent shares
Haulm Intake	Fitted with rubber anti-roll flaps
Haulm Guides	Via adjustable plastic covered spring loaded straight fingers

Haulm Removing Roller	One haulm extraction roller
Separation	Galaxy unit with 3 pairs of 14 fingered stars and contra rotating, mechanically driven
Transfer	Spreader stars
Cart Elevator	Variable speed, hydrulically driven and high reach, with a swan neck. Fully retractable for transport. Elevator rods covered.
Wheel Steering	Hydraulic Ram with track rods
Wheels	12.5 x 18 10 Ply Trac-Grip
Levelling	Hydraulic Ram
Length Working	7.4Std (8.3m Fitted P.O.B)
Hydraulic Source - Tractor	External service, approx 40 1/min
Row Widths	26-36ins or 66-90cm
Separation Width	1500mm
Tyres	12.5 x 18 12ply Trac-Grip
Transport Height	3.2m standard (7.4m with canopy fitted)
PTO & Connection Stub	540rpm - 1 3/8ins 6 spline
Electrical requirement	12v d.c from tractor, -ve earth
Weight Unladen	Approx 3.5 tonnes
Width- working	(36" rows) 3.38m

Standen QM Harvester Optional Equipment Web Web cleaner VariousSizesofbolton centreshares for beds. Various size multi-**Shares** shares Mechanically adjustable agitation available to suit field conditions. Agitator Electric pitch adjustment. Hydraulically driven to move clod/crop evenly across the web area Oscillator (Not compatible with VariWeb) Large rubber fingers fitted to an adjustable frame to assist clod **Clod Fingers** breakdown Sieving Web VariWebcan be fitted to eliminate rollback on hillsides or sandy soils Separation Galaxy with 18 finger stars- shaft speed monitor Cart Elevator Drop arrester (box filling chute) In line table side picking for 2 people or canopy and frame to suit Picking Off Table above P.O.B