



**Telephone** +44 (0) 1353 661111  
**Fax** +44 (0) 1353 662370  
**Email** [sales@standen.co.uk](mailto:sales@standen.co.uk)

## Standen QM Potato Harvester

| Standen QM Harvester Standard Specification |   |
|---|---|
| Power Requirements                          | From 65hp   |
| Open Front End                              | 1500mm wide front share and web for crops grown in 26-36" rows or beds            |
| Controls                                    | Electronic in-cab control box   |
| Drawbar                                     | Hydraulic Adjustment  |
| Depth Control                               | Automatic depth sensing   |
| Intake Discs                                | Independent spring loaded fitted on a live floating chassis. Fitted with scrapers |
| Shares                                      | 1 or 2 piece independent shares   |

|                            |  |
|----------------------------|--|
| Haulm Intake               | Fitted with rubber anti-roll flaps   |
| Haulm Guides               | Via adjustable plastic covered spring loaded straight fingers  |
| Haulm Removing Roller      | One haulm extraction roller  |
| Separation                 | Galaxy unit with 3 pairs of 14 fingered stars and contra rotating, mechanically driven   |
| Transfer                   | Spreader stars   |
| Cart Elevator              | Variable speed, hydraulically driven and high reach, with a swan neck. Fully retractable for transport. Elevator rods covered. |
| Wheel Steering             | Hydraulic Ram with track rods  |
| Wheels                     | 12.5 x 18 10 Ply Trac-Grip   |
| Levelling                  | Hydraulic Ram  |
| Length Working             | 7.4Std (8.3m Fitted P.O.B)   |
| Hydraulic Source - Tractor | External service, approx 40 l/min  |
| Row Widths                 | 26-36ins or 66-90cm  |
| Separation Width           | 1500mm   |
| Tyres                      | 12.5 x 18 12ply Trac-Grip  |
| Transport Height           | 3.2m standard (7.4m with canopy fitted)  |
| PTO & Connection Stub      | 540rpm - 1 3/8ins 6 spline   |
| Electrical requirement     | 12v d.c from tractor, -ve earth  |
| Weight Unladen             | Approx 3.5 tonnes  |

|                             |                  |
|-----------------------------|------------------|
| Width- working              | (36" rows) 3.38m |
| Width - Transport Container | 2.26m            |

## Standen QM Harvester Optional Equipment

|                   |  |
|-------------------|--|
| Web               | Web cleaner  |
| Shares            | Various Sizes of bolton centreshares for beds. Various size multi-shares                         |
| Agitator          | Mechanically adjustable agitation available to suit field conditions. Electric pitch adjustment. |
| Oscillator        | Hydraulically driven to move clod/crop evenly across the web area (Not compatible with VariWeb)  |
| Clod Fingers      | Large rubber fingers fitted to an adjustable frame to assist clod breakdown                      |
| Sieving Web       | VariWeb can be fitted to eliminate rollback on hillsides or sandy soils                          |
| Separation        | Galaxy with 18 finger stars- shaft speed monitor   |
| Cart Elevator     | Drop arrester (box filling chute)  |
| Picking Off Table | In line table side picking for 2 people or canopy and frame to suit above P.O.B                  |