



Standen T3 Harvester

Standen T3 Harvester Standard Specification

Chassis	Open plan, heavy-duty welded construction
Power Requirements	200hp+tractor, 12v electrics
Drives	All-hydraulic variable speed, in-cab controls
In-Cab Control System	Touch screen, programmeable, joystick console, CAB-bus electronics
Drawbar	Hydraulic adjustment, 1-row offset to left or right, in-cab control
Depth Control	Automatic with in-cab control override
Depth Sensing	2x Hydraulic driven steel drum rollers
Intake Discs	6 x springloaded with heavy-duty bearings
Shares	3x 2-piece
Haulm Intake Rollers	2 at outer discs, centre rubber flaps

Digging Web	36mm pitch,2.5m wide
Sieving Web	40mm pitch, 2.5m wide
Sieving Web Adjustment	VariSep, primary/secondary web step adjustment, in-cab control
Sieving Web Agitation	4 x high frequency, adjustable in pairs, in-cab control
Haulm Guides	Curved tines at top of secondary web
Haulm Removing Roller	Hydraulic drive, rubber covered, adjustable, reversible,in-cab control
Separation	2 x OMEGA units, each with 4 x fluted rollers, 4 x rubber or steel clod rollers
Transfer 1	Stainless steel roller
Transfer 2	3 x Spreader webs (graduated)
Discharge Elevator	Double hydraulic folding, 1300mm wide, in-cab controls
Hydraulic Oil Reservoir	High capacity chassis integrated
Hydraulic Oil Cooling	Thermostatically controlled electric fan oil cooler + chassis mounted cooling
Hydraulic Oil Pumps	4x high capacity load sensing pumps
Hydraulic Protection 1	4 x Suction filters protect pumps
Hydraulic Protection 2	Individual pre-filters fitted in valve lines
Wheel Rotation	RH, Rotates 180 degrees (field opening/transport) in-cab control

Wheel Steering	Hydraulic, 30 degrees, automatic self-centring, in-cab controls
Wheel Drives	Hydraulic, in-cab controls = assist/constant/power boost
Wheels	Steel rims Tyres: 700 x 45 26.516-ply tyres
Levelling	Hydraulic, in-cab controls
Length	11.35m
Width - Working	4.26m
Width - Transport	3.40m
Height	3.8m
Weight	12640kg
Weight at drawbar	2480kg
Shipping Dimensions	Length 11.35m x Width 3.4m x Height 3.8m

Standen T3 Harvester Optional Equipment

Shares	Full-width bed shares
Haulm Intake Rollers	For centre row in lieu of rubber flaps
Sieving Web	36,45 or 50mm Pitches
Sieving web Cleaner	Rubber block type or cadge roller
Clod Fingers	Sweeping fingers, hydraulic, variable speed

Fluted Rollers	6mm, 10mm (standard) or 20mm flutes
Elevator	Automatic height control
Sorting Tables	EasiPic, 3/4 person