



## Standen Powavator Bed Tiller

### Standard Powavator Bed Tiller Features:

Model	150/170	150/180	400/70/70
Bed Widths	1 bed of 1.8m	1 bed of 2.0m	2 beds of 1.8m (one on each side of tractor)
Maximum Tractor HP	170	170	400
Rigid or Hydraulic folding	Rigid	Rigid	Folding
Rotor Type Available	All	All	All

Model	400/140	400/200	400/240	150/70 Front Mounted Incorporator	150/95 Front Mounted Incorporator
Bed Widths	2 beds of 1.8m	3 beds of 1.8m	3 beds of 2.0m	1 bed of 1.8m	1 bed of 2.4m

Maximum Tractor HP	400	400	400	170	170
Rigid or Hydraulic Folding	Folding	Folding	Folding	Rigid	Rigid
Rotor Type Available	All	All	All	Stubble rotor	Stubble rotor

Oil immersed Gear Side drives

Strong shearbolt legs

Heavy duty gearboxes, speedset with changeable gears for different rotor speeds (excluding 400 series) or TORQUE + Heavy duty fixed speed

Heavy duty rotors

### Optional Powavator Bed Tiller Features:

Convex bodies with bolt-on wear strips

Auto-Reset MD legs

Choice of rotors; Speed Blade, L Blade, Stubble Rotor, Spike Tine, Rapid Pin Fixing (Speed or L Blade only), Single Bolt Fixing (Speed or L Blade only)

Depth Wheels

Bed forming Hoods (to enable planting directly behind the tiller)