



Standen QM Windrower

Standen QM Harvester Standard Specification

Power Requirements	From 65hp for Galaxy Separators; 100hp for OMEGA Separators
Windrow Conveyor	500mm wide with the ability to discharge onto either adjacent bed or one bed further over. The end section is adjustable for angle to reduce crop drop, fully foldable for transport.
Open Front End	1500mm wide front share and web for crops grown in 26-36" rows or beds
Controls	Electronic in-cab control box
Drawbar	Hydraulic Adjustment
Depth Control	Automatic depth sensing
Intake Discs	Independent spring loaded fitted on a live floating chassis. Fitted with scrapers
Shares	1 or 2 piece independent shares

Haulm Intake	Fitted with rubber anti-roll flaps
Haulm Guides	Via adjustable plastic covered spring loaded straight fingers
Haulm Removing Roller	One haulm extraction roller
Separation	<p>Galaxy with 3 pairs of 14 finger stars and contra rotating extraction rollers, mechanically driven.</p> <p>Or</p> <p>OMEGA with 5 Scroll Rollers and 4 Extraction Rollers. The unit is adjustable for angle from the tractor cab. The Extraction Rollers are height adjustable and are reversible. The Scroll Rollers and Extraction Rollers are speed variable from the tractor cab. The Omega is fully hydraulically driven from its own machine mounted hydraulic supply.</p>
Transfer	Spreader stars
Cart Elevator	Variable speed, hydraulically driven and high reach, with a swan neck. Fully retractable for transport. Elevator rods covered.
Wheel Steering	Hydraulic Ram with track rods
Wheels	12.5 x 18 10 Ply Trac-Grip
Levelling	Hydraulic Ram
Length Working	8.0m (8.9m with POB fitted)
Hydraulic Source - Tractor	External service, approx 40 l/min
Row Widths	26-36ins or 66-90cm
Separation Width	1500mm

Tyres	12.5 x 18 12ply Trac-Grip
Transport Height	3.6m with discharge elevator, 2.1m for windrower machine
PTO & Connection Stub	540rpm - 1 3/8ins 6 spline
Electrical requirement	12v d.c from tractor, -ve earth
Weight Unladen	TBC
Width- working	(36" rows) 3.38m
Width - Transport Container	2.26m

Standen QM Windrower Optional Equipment	